

# MALAGA Serisi



575



577



## QUALITY

Product Definition	ISO 2424	Tufted Loop Pile
Gauge	1/10"	
No. of Tufts	ISO 1763	$\pm 177750/m^2$ (-7.5% , +10%) 100%
Pile Fibre	ISO 2424	Polypropylene
Pile Weight	ISO 8543	660 gr/m <sup>2</sup> $\pm 5%$ ( $\pm 10$ oz/yd <sup>2</sup> )
Pile Height	ISO 1765	3.0 mm $\pm 5%$
Primary Backing	ISO 2424	PA/PES non-woven
Tile Backing		Polyflex non-woven fabric
Total Thickness	ISO 1765	6.0 mm $\pm 5%$
Total Weight	ISO 8543	3800 gr/m <sup>2</sup> $\pm 7.5%$ ( $\pm 109$ oz/yd <sup>2</sup> )
Tile Size	EN 986	50 x 50 cm ( $\pm 19.7$ x $19.7$ )
Tiles per box		20
Use Classification	EN 1307	Contract Class 32
Abrasion		Pass
Vettermann Test	ISO 10361	Pass
Dimensional Stability	ISO 10361	Pass
Thermal Isolation		

## ELEKTROSTATIC PROPERTIES

Static Loading	ISO 2424	Anti-static
Flame Properties		
Reaction to Fire	ISO 1763	
Hot Metal Nut Test	EN130501-1	Cfl-S1

## COLOUR FASTNESS PROPERTIES

Light	ISO 105 B02	>5.0
Rubbing, Dry	ISO 105 X12	>4.0
Rubbing, Wet		
Shampoo		
Water	ISO 105 E01	>4.0

## GENERAL

Recommended Maintenance  
Pile Direction  
Laying Instructions

Best results are obtained when cleaned with a dry shampoo method. Detailed advice can be found on the back of each tile. Best results are obtained when laid on a clean, dry, level surface. Tiles require an underlay, padding, gluing or sewing and may be laid loose on a flat, dry, non-slippery floor, when tiles are laid on concrete, vinyl or in open areas larger than 10 m<sup>2</sup> it is advisable to use double sided adhesive tape on every 5th row or 4

