

SANTORINI Serisi



3276



3278



QUALITY

Product Definition	ISO 2424	Tufted Loop Pile
Gauge		1/10"
No. of Tufts	ISO 1763	± 177750/m ² (-7.5%, +10%)
Pile Fibre	ISO 2424	100% Polypropylene
Pile Weight	ISO 8543	660 gr/m ² ±5% (±10 oz/yd ²)
Pile Height	ISO 1765	3.0 mm
Primary Backing	ISO 2424	non-woven
Tile Backing		Polyflex
Total Thickness	ISO 1765	5.0 mm
Total Weight	ISO 8543	3660 gr/m ² (± 15%)
Tile Size	EN 986	50 x 50 cm (± 0.2%)
Tiles per box		20
Use Classification	EN 1307	Contract Class 32
Abrasion	ISO 10361	Pass
Vettermann Test	ISO 10361	Pass
Dimensional Stability		Pass
Thermal Isolation		

ELEKTROSTATİK PROPERTIES

Static Loading	ISO 2424	Anti-static
Flame Properties		
Reaction to Fire	ISO 1763	ClI-SI
Hot Metal Nut Test	EN130501-1	

COLOUR FASTNESS PROPERTIES

Light	ISO 105 B02	>5.0
Rubbing, Dry	ISO 105 X12	>4.0
Rubbing, Wet		
Shampoo		
Water	ISO 105 E01	>4.0

GENERAL

Recommended Maintenance	
Pile Direction	
Laying Instructions	

Best results are obtained when cleaned with a dry-foam-spoon method. Disinfectant sprays are permitted on the back of each tile. Best results are obtained when laid over a concrete subfloor. Tiles require an underlay, making gluing or sewing and may be laid loose on a flat, dry, non-slippery floor. When tiles are laid on carpet, vinyl or in open areas larger than 30 m² it is advisable to use double sided adhesive tape on every 6th row or 4.

